



EC Declaration of Conformity
(Construction Products Directive)

Address of Manufacturer :

Knauf Insulation Ltd.,
PO Box 10,
Stafford Rd.,
St. Helens,
Merseyside
WA10 3NS
U.K.

Notified Certification Body :

BSI Product Services
(Appr. Body ID 0086)

Maylands Ave.,
Hemel Hempstead,
Herts.,
HP2 4SQ
U.K.

Product Description & Use :

Factory made mineral wool thermal insulation in the form of rolls, batts, boards, and slabs for use in thermal insulation of buildings.

See attachment for product/trade names and declared values.

Particular provisions for the end use of the product :

None

Conforms to the Provisions of :

Construction Products Directive
EN 13162:2001 Thermal insulation products for buildings – Factory made mineral wool (MW) products – made with ECOSE™ Technology binder.

Certificate of Conformity No :

0086-CPD-466627 for products with A1 and A2 Euroclass

Signed on behalf of manufacturer:

Name : Ian Gornall **Position :** Plant Manager

For the period 01/01/09 to 30/06/09.

EC konformitetsdeklaration
(Direktiv för konstruktionsprodukter)

Tillverkarens adress: Knauf Insulation Ltd., PO Box 10, Stafford Rd., St. Helens, Merseyside WA10 3NS U.K.	Notifierad certifieringsorganisation: BSI Product Services (Certifikationsorganets ID 0086) Maylands Ave. Hemel Hempstead Herts. HP2 4SQ U.K.
--	---

Produktbeskrivning och användningsområde:

Fabrikstillverkad värmeisolerande mineralull i rullar, plattor och skivor för användning vid värmeisolering av byggnader.

Se bilaga för produktnamn och deklarerade värden.

Specifika föreskrifter för produktens användning:


Inga

Överensstämmer med föreskrifter:

Konstruktionsproduktdirektiv
EN 13162:2001 Värmeisolerande produkter för byggnader – Fabrikstillverkad mineralull (MW) tillverkad med ECOSE® technology bindemedelsteknologi.

Certifikatnummer: 0086-CPD-466627 för A1 och A2 Euroclass.

Signerad för tillverkaren



Navn: Ian Gornall

Stilling: Anläggningschef, St Helens

Dato: 10/06/09

Declaration of Conformity - Products supplied to UK and Ireland (1)

Product Name / Trade Name	Thickness Range (mm)	Reaction to Fire Class (Euroclass)	Thermal Conductivity (W/mk)	Designation Code
Loft Roll Range				
Earthwool CarbonZero Roll	60 - 250	A1	0.044	MW-EN 13162-T1
Loft Roll 270mm	270	A1	0.044	MW-EN 13162-T1
Loft Roll 44 (Combi-cut, Ready cut, uncut)	60 - 250	A1	0.044	MW-EN 13162-T1
Loft Roll 40 (Combi-cut, Ready-cut)	60 - 250	A1	0.040	MW-EN 13162-T1
Universal Roll	60 - 250	A1	0.044	MW-EN 13162-T1
FactoryClad Range				
FactoryClad 40	60 - 220	A1	0.040	MW-EN 13162-T1
FactoryClad 37	80 - 180	A1	0.037	MW-EN 13162-T1
FactoryClad 35	40 - 140	A1	0.035	MW-EN 13162-T1
FactoryClad 32	80 - 100	A1	0.032	MW-EN 13162-T1
FrameTherm Roll Range				
FrameTherm Roll 40	90 - 140	A1	0.040	MW-EN 13162-T1
FrameTherm Roll 35	90 - 140	A1	0.035	MW-EN 13162-T1
FrameTherm Roll 32	90	A1	0.032	MW-EN 13162-T1
SteelTherm Roll Range				
SteelTherm Roll 40	60 - 200	A1	0.040	MW-EN 13162-T1
Rafter Roll				
Rafter Roll 32	50 - 100	A1	0.032	MW-EN 13162-T1
DriTherm Range				
DriTherm 37 Standard	65 - 150	A1	0.037	MW-EN 13162-T4-WS
DriTherm 37 Standard (50mm)	50	A1	0.035	MW-EN 13162-T4-WS
DriTherm 34 Super	65 - 100	A1	0.034	MW-EN 13162-T4-WS
DriTherm 32 Ultimate	65 - 100	A1	0.032	MW-EN 13162-T4-WS
DriTherm Cavity Slab 36	150	A1	0.036	MW-EN 13162-T4-WS
Room-in-Roof Roll Range				
Room-in-Roof Roll 37	100 - 200	A2	0.037	MW-EN 13162-T1
Room-in-Roof Roll 32	100	A2	0.032	MW-EN 13162-T1

Declaration of Conformity - Products supplied to UK and Ireland (2)

Product Name / Trade Name	Thickness Range (mm)	Reaction to Fire Class (Euroclass)	Thermal Conductivity (W/mk)	Designation Code
Universal Slab Range				
Universal Slab CS24	50 - 100	A1	0.035	MW-EN 13162-T4
Universal Slab CS32	25 - 100	A1	0.034	MW-EN 13162-T4
Universal Slab CS48	25 - 75	A1	0.032	MW-EN 13162-T4
FrameTherm Slab Range				
FrameTherm Slab 43	90 - 140	A1	0.043	MW-EN 13162-T4
FrameTherm Slab 38	90 - 140	A1	0.038	MW-EN 13162-T4
FrameTherm Slab 35	90 - 140	A1	0.035	MW-EN 13162-T4
FrameTherm Slab 32	50 - 90	A1	0.032	MW-EN 13162-T4
Roof Product Range				
Kalzip Quilt 44	60 - 200	A1	0.044	MW-EN 13162-T1
Kalzip Plus 40	100 - 180	A1	0.040	MW-EN 13162-T1
Kalzip Plus 37	80 - 180	A1	0.037	MW-EN 1316-T1
Kalzip Plus 35	40 - 140	A1	0.035	MW-EN 13162-T1
Kalzip Plus 32	110 - 120	A1	0.032	MW-EN 13162-T1
Rigidal HP/LO37	140	A1	0.037	MW-EN 13162-T1
Knauf UK Retail				
Focus Payless Loft Roll	100	F	0.044	MW-EN 13162-T1
Space Combi Roll	100 - 170	A1	0.044	MW-EN 13162-T1
Wickes Loft Insulation Roll	100 - 170	A1	0.044	MW-EN 13162-T1
Wickes Cavity Slab 37	100	A1	0.037	MW-EN 13162-T4-WS

Declaration of Conformity – Products supplied to mainland Europe

Product Name / Trade Name	Thickness Range (mm)	Reaction to Fire Class (Euroclass)	Thermal Conductivity (W/mk)	Designation Code
TI 212	80 - 200	F	0.040	MW-EN 13162-T2
Thermolan Classic 040	100 - 200	A1	0.040	MW-EN 13162-T1
Thermolan Classic 044	100 - 200	A1	0.044	MW-EN 13162-T1
TI 135 U	200	A1	0.035	MW-EN 13162-T2
TI 140 U	200	A1	0.039	MW-EN 13162-T2

Declaration of Conformity – Products supplied to the Nordic Region

Product Name / Trade Name	Thickness Range (mm)	Reaction to Fire Class (Euroclass)	Thermal Conductivity (W/mk)	Designation Code
EcoBlanket Range				
EcoBlanket 037	45 - 250	A1	0.037	MW-EN 13162-T1
EcoBlanket 035	45 - 250	A1	0.035	MW-EN 13162-T1
EcoBatt Range				
EcoBatt 037	45 - 250	A1	0.037	MW-EN 13162-T4
EcoBatt 035	50 - 200	A1	0.035	MW-EN 13162-T4
EcoBatt Mur Isolering Range (Denmark)				
EcoBatt Mur Isol 037	100 - 190	A1	0.037	MW-EN 13162-T4-WS
EcoBatt Mur Isol 034	125	A1	0.034	MW-EN 13162-T4-WS
Space Range – Roll and Slab				
Space Roll 039	45 - 150	A1	0.039	MW-EN 13162-T1
Space Roll 037	45 - 200	A1	0.037	MW-EN 13162-T1
Space Roll 035	70 - 150	A1	0.035	MW-EN 13162-T1
Space Slab 037	45 - 200	A1	0.037	MW-EN 13162-T4
Space Slab 035	50 - 200	A1	0.035	MW-EN 13162-T4
Drev (Cavity Closer)				
Drev 25mm	25	A1	0.036	MW-EN 13162-T1
Drev 50mm	50	A1	0.037	MW-EN 13162-T1